

Odyssey 3

PROTECTION GUARANTEED



ACE Security's *Odyssey™* external sounder and strobe series has been further enhanced by the addition of the stunning *Odyssey 3*. Environmentally sealed microprocessor technology, twin piezo sounders and triple tamper protection ensure uncompromising performance. Competitively priced and easy to install, the *Odyssey 3* is the clear choice for all professional installations.

Outstanding features include:

- ✓ 115dB VOLUME
- ✓ IP65 SEALED ELECTRONICS
- ✓ PATENTED SAFETY ENGINEER HOLD-OFF MODE
- ✓ ADVANCED MICROPROCESSOR TECHNOLOGY
- ✓ REVOLUTIONARY SCREW RETENTION SYSTEM
- ✓ POLYCARBONATE CONSTRUCTION
- ✓ SELECTABLE SAB/SCB MODE
- ✓ SCREW, LID & WALL TAMPER
- ✓ TWIN ALTERNATING LEDs
- ✓ STROBE TUBE SAVER



SECURITY



ODYSSEY 3 FEATURES



Terminal Block Cover

Advanced Microprocessor Technology

The *Odyssey 3* incorporates advanced microprocessor technology, ensuring unsurpassed reliability and responsiveness.

Patented Engineer Hold-off Mode

Installation and maintenance is made quick, simple and safe by a revolutionary patented safety engineer hold-off mode. On power-up the hold-off mode is automatically enabled, preventing the unit from sounding until the tamper circuit is secure. This enables "one trip up the ladder" installation. Hold-off mode can be re-invoked at any time from the control panel, ensuring easy maintenance and verification.



Twin Piezo Sounders



IP65 Sealed Electronics

Stylish "shield" design vertically mounting sounder & strobe



Powerful Strobe Indication



Combined Wall & Lid Tamper

IP65 Sealed Electronics Module

The advanced electronic module of the *Odyssey 3* is protected by a robust inner cover assembly with gasket seal. This increases protection from dust and moisture, sealing to IP65 rating which enables prolonged exposure to harsher environments without compromising performance or functionality.

Triple Tamper Detection

Lid, wall and screw tamper detection is provided as standard. Wall tamper is derived from a fixing screw location, removing the need to drill additional fixing holes and providing optimum reliability. Screw tamper provides the earliest possible indication of unauthorised access to the unit.



Screw Tamper Detection



Integrated Screw Cover Cap

Specifications

Supply Voltage:	13.7V (nominal)
Current Drain	
Quiescent (inc charging):	15mA
Strobe:	100mA
Sounder:	425mA
Battery:	Nical Stalk, 7.2Vdc, 280mAh
Strobe:	1W, 1Hz Flash Rate
Dimensions:	315mm x 306mm x 78mm
Packed Weight:	1750g (45oz) approx



EUROPEAN STANDARDS

Safety: Conforms to European Union (EU) Low Voltage Directive (LVD) 73/23/EEC (amended by 93/68/EEC).

EMC: Conforms to European Union (EU) Electro-Magnetic Compatibility (EMC) Directive 88/336/EEC (amended by 92/31/EEC and 93/68/EEC).

Approved to BS EN 55022 Class B and BS EN 50130-4 : 1996.

The CE mark indicates that this product complies with the European requirements for safety, health, environmental and customer protection.



SECURITY

